

Enphase Envoy-S Series

The **Enphase Envoy-S™** communications gateway delivers solar production and energy consumption data to Enphase Enlighten™ monitoring and analysis software for comprehensive, remote maintenance and management of the Enphase Microinverter System.

With revenue grade production metering and consumption monitoring options, Envoy-S is the platform for total energy management and integrates with the Enphase AC Battery™.



Smart

- Enables web-based monitoring and control
- Bidirectional communications for remote upgrades

Simple

- Easy system configuration using Enphase Installer Toolkit™ mobile app
- Flexible networking with Wi-Fi, Ethernet, or cellular

Reliable

- Designed for installation indoors or outdoors
- Five-year warranty



LISTED

To learn more about Enphase offerings, visit enphase.com

Enphase Envoy-S

MODEL NUMBERS

Enphase Envoy-S Standard™
ENV-S-AB-120-A Enphase Envoy-S communications gateway with basic PV production monitoring (+/- 5%).

Enphase Envoy-S Metered™
ENV-S-AM1-120 Enphase Envoy-S communications gateway with integrated revenue grade PV production metering (ANSI C12.20 +/- 0.5%) and optional consumption monitoring (+/- 2.5%).

ACCESORIES (Order Separately)

Enphase Mobile Connect™
CELLMODEM-01 Plug and play industrial grade cellular modem with five-year data plan for systems up to 60 microinverters. (Available in the US, Canada, Mexico, Puerto Rico, and the US Virgin Islands, where there is adequate cellular service in the installation area.)

Consumption Monitoring CT
CT-200-SPLIT For use with ENV-S-AM1-120, split-core current transformers enable whole home consumption metering (+/- 2.5%).

POWER REQUIREMENTS

Cord connected 120 VAC, 60 Hz (ENV-S-AB-120-A)
Max 15 A overcurrent protection required

Hardwired 120 VAC, 60 Hz (ENV-S-AB-120-A)
120/240 VAC split-phase (ENV-S-AM1-120)
Max 15 A overcurrent protection required

CAPACITY

Number of microinverters polled Up to 600

MECHANICAL DATA

Dimensions (WxHxD) 21.3 x 12.6 x 4.5 cm (8.4" x 5" x 1.8")

Weight 17.6 oz (498 g)

Ambient temperature range -40° to 65° C (-40° to 149° F)
-40° to 46° C (-40° to 115° F) if installed in an enclosure

Environmental rating IP30. For installation indoors or in an NRTL-certified, NEMA type 3R enclosure.

Altitude To 2000 meters (6,560 feet)

INTERNET CONNECTION OPTIONS

Integrated Wi-Fi 802.11b/g/n

Ethernet 802.3, Cat5E (or Cat 6) UTP Ethernet cable (not included)

Mobile Optional, CELLMODEM-01 (not included)

COMPLIANCE

Compliance UL 916
CAN/CSA C22.2 No. 61010-1
47 CFR, Part 15, Class B, ICES 003
IEC/EN 61010-1:2010,
EN50065-1, EN61000-4-5, EN61000-6-1, EN61000-6-2
Metering: ANSI C12.20 accuracy class 0.5 (ENV-S-AM1-120)

To learn more about Enphase offerings, visit enphase.com

© 2016 Enphase Energy. All rights reserved. All trademarks or brands used are the property of Enphase Energy, Inc.
04/18/2016

